



LED BULB

ANGLE-ADJUSTABLE SERIES



MR16



PAR30

UNIQUE FEATURE

**Patented
angle-adjustable Design
Dimmable & Non-dimmable
Competitive Price
Unique Design**

Application:

MR16:

Suitably design for spot and general application in Hospitals, Retail Industries and in Public Areas such as Corridors, Stairway, Lobby and Reception Areas. Ensures minimum maintenance cost in Hotels, Restaurants and Cafes.

Par30:

Ideal LED solutions in Hotels, Malls and Supermarkets. Suitable for Directional Light Source, Exhibitions, Department Store and Landscape Lighting.



LED BULB MR16/PAR LAMP SERIES

IMAGE MODEL

ANGLE-ADJUSTABLE SERIES (DIM/NON-DIM)

JED LR16-06W-A GU10 MR16; JED LR16-06W-A GU5.3 MR16



COLOR TEMP (K)	2700-6500
RENDERING INDEX (ra)	80
MAX. LUMINOUS INTENSITY (cd)	400
LUMINOUS FLUX (lm)	350
EFFICIENCY lm/w	58
BEAM ANGLE (°)	25°, 40°, 55°
LAMP LIFE (hrs)	30,000

WATTAGE (w)	6
POWER FACTOR	0.9
DIAMETER (mm)	50
LENGTH (mm)	60
LAMP BASE	GU10 ; GU5.3
VOLTAGE	100-240

JED LR30-15W-A PAR30



COLOR TEMP (K)	2700-6500
RENDERING INDEX (ra)	80
MAX. LUMINOUS INTENSITY (cd)	3000
LUMINOUS FLUX (lm)	800
EFFICIENCY lm/w	60
BEAM ANGLE (°)	15°, 30°, 60°
LAMP LIFE (hrs)	30,000

WATTAGE (w)	15
POWER FACTOR	0.9
DIAMETER (mm)	95
LENGTH (mm)	120
LAMP BASE	E27
VOLTAGE	100-240

SPOT LIGHT SERIES (DIM/NON-DIM)

JED LR11-03W01 MR11



COLOR TEMP (K)	2700-6500
RENDERING INDEX (ra)	80
MAX. LUMINOUS INTENSITY (cd)	450
LUMINOUS FLUX (lm)	200
EFFICIENCY lm/w	65
BEAM ANGLE (°)	30°
LAMP LIFE (hrs)	30,000

WATTAGE (w)	3
DIAMETER (mm)	35
LENGTH (mm)	35
LAMP BASE	G4
VOLTAGE	12

JED LR16-07W01 MR16 ; JED LR16-07W06 MR16



COLOR TEMP (K)	2700-6500
RENDERING INDEX (ra)	80
MAX. LUMINOUS INTENSITY (cd)	360 ; 350
LUMINOUS FLUX (lm)	450 ; 500
EFFICIENCY lm/w	64 ; 70
BEAM ANGLE (°)	60
LAMP LIFE (hrs)	30,000

WATTAGE (w)	7
POWER FACTOR	0.9
DIAMETER (mm)	50
LENGTH (mm)	60
LAMP BASE	GU10 ; GU5.3
VOLTAGE	100-240

JED LR30-15W01 (45°) PAR30; JED LR30-15W02 (30°) PAR30; JED LR30-15W03 (15°) PAR30



COLOR TEMP (K)	3000-5000
RENDERING INDEX (ra)	85
MAX. LUMINOUS INTENSITY (cd)	1500 ; 3000 ; 7500
BEAM ANGLE (°)	45° ; 30° ; 15°
LAMP LIFE (hrs)	30,000

WATTAGE (w)	15
POWER FACTOR	0.8
DIAMETER (mm)	95
LENGTH (mm)	120
LAMP BASE	E27
VOLTAGE	100-240

JED LR38-20W01 PAR38



COLOR TEMP (K)	2700-6500
RENDERING INDEX (ra)	82
MAX. LUMINOUS INTENSITY (cd)	1350
BEAM ANGLE (°)	45°
LAMP LIFE (hrs)	30,000

WATTAGE (w)	20
POWER FACTOR	0.9
DIAMETER (mm)	120
LENGTH (mm)	139
LAMP BASE	E27
VOLTAGE	100-240



Products Distributed by:



INNOVALITE
ELECTRICAL ENTERPRISE

2F Unit F Princeton Square Bldg.,
#35 C. Raymundo Avenue, Rosario, Pasig City, Philippines
Phone Nos.: (02)642-4739 / (02)915-2145; Fax: (02)628-0605 / (02)900-0228
Website: www.innovalitephilippines.com; E-mail: innovalite@yahoo.com