




FLOODLIGHT FIXTURE IP65



Features

- Material: Aluminum Alloy Housing
- Luminous Efficiency: 80-90 Lm/w
- Color Rendering: Ra>80
- Ingres Protection: IP65

Application:

- Bridges, Tunnel, High Mast, Billboard, Roadway, Buildings, Gardens



FLOODLIGHT FIXTURE IP65

IMAGE	MODEL NO.	LED POWER (W)	POWER FACTOR	LIGHT SOURCE	VOLTAGE (V)	LUMINOUS FLUX (lm)	BEAM ANGLE(°)	COLOR TEMP. (CRI)	LIFETIME (HRS)	WORKING TEMP.	SRP(Php)
	GRL7181	10	>0.9	ONE POWERFUL LED LIGHT	85-265V 50/60Hz	700-800	120°	2700-7000 (>70)	50,000	-40°C~50°C	-
	GRL7182	30	>0.9	ONE POWERFUL LED LIGHT	85-265V 50/60Hz	2100-2400	120°	2700-7000 (>70)	50,000	-40°C~50°C	-
	GRL7183	50	>0.9	ONE POWERFUL LED LIGHT	85-265V 50/60Hz	3500-4000	120°	2700-7000 (>70)	50,000	-40°C~50°C	-
	GRL7184	100	>0.9	ONE POWERFUL LED LIGHT	85-265V 50/60Hz	7000-8000	120°	2700-7000 (>70)	50,000	-40°C~50°C	-
	GRL7011	10	>0.9	ONE POWERFUL LED LIGHT	85-265V 50/60Hz	700-800	120°	2700-7000 (>70)	50,000	-40°C~50°C	-
	GRL7012	20	>0.9	ONE POWERFUL LED LIGHT	85-265V 50/60Hz	1400-1600	120°	2700-7000 (>70)	50,000	-40°C~50°C	-
	GRL7183	30	>0.9	ONE POWERFUL LED LIGHT	85-265V 50/60Hz	2100-2400	120°	2700-7000 (>70)	50,000	-40°C~50°C	-
	GRL7014	50	>0.9	ONE POWERFUL LED LIGHT	85-265V 50/60Hz	3500-4000	120°	2700-7000 (>70)	50,000	-40°C~50°C	-
	GRL7022	80	>0.9	ONE POWERFUL LED LIGHT	85-265V 50/60Hz	5600-6400	120°	2700-7000 (>70)	50,000	-40°C~50°C	-



Products Distributed by:



INNOVALITE
ELECTRICAL ENTERPRISE

2F Unit F Princeton Square Bldg.,
#35 C. Raymundo Avenue, Rosario, Pasig City, Philippines
Phone Nos.: (02)642-4739 / (02)915-2145; Fax: (02)628-0605 / (02)900-0228
Website: www.innovalitephilippines.com; E-mail: innovalite@yahoo.com