



LED SERIES CEILING LIGHT



NIGHT-LIGHT
MODEL



COLOR TEMPERATURE
CONTROL



FLEXIBLE BRIGHTNESS
ADJUSTMENT



HUMAN BODY
SENSOR



REMOTE OPERATED



DESIGN FEATURES

- **SUPER SLIM**
- **ADJUSTABLE FRAME**
- **QUICK & EASY INSTALLATION**

APPLICATION

- **RESIDENTIAL, OFFICE AND HOSPITAL APPLICATION**



LED SERIES CEILING LIGHT

WITH HUMAN BODY SENSOR



JED MX007 HUMAN BODY SENSOR (alternative)

WATTAGE (W)	8	INITIAL LUMENS (Lm)	600
INPUT VOLTAGE	110/220 VAC	LUMEN EFFICIENCY (Lm/w)	75
FREQUENCY	50/60 Hz	CRI (Ra)	80
LIFE TIME	35,000 Hrs	BEAM ANGLE (°)	120°
WORK TEMPERATURE	-25°C/-45°C	DIMENSION (mm)	Ø 260 X 61.5
COLOR TEMP (K)	4000-5700		Ø 260 X 64.0
			Ø 210 X 50.0



JED MX501 HUMAN BODY SENSOR (alternative)

WATTAGE (W)	16	INITIAL LUMENS (Lm)	1100
INPUT VOLTAGE	110/220 VAC	LUMEN EFFICIENCY (Lm/w)	68
FREQUENCY	50/60 Hz	CRI (Ra)	80
LIFE TIME	35,000 Hrs	BEAM ANGLE (°)	120°
WORK TEMPERATURE	-25°C/-45°C	DIMENSION (mm)	Ø 346 x 41
COLOR TEMP (K)	3000-6500		



JED MX601 COLOR TEMPERATURE CONTROL (alternative)

WATTAGE (W)	48	INITIAL LUMENS (Lm)	3700
INPUT VOLTAGE	110/220 VAC	LUMEN EFFICIENCY (Lm/w)	77
FREQUENCY	50/60 Hz	CRI (Ra)	80
LIFE TIME	35,000 Hrs	BEAM ANGLE (°)	120°
WORK TEMPERATURE	-25°C/-45°C	DIMENSION (mm)	Ø 524 x 42
COLOR TEMP (K)	3000-6500		



JED MX602

WATTAGE (W)	54	INITIAL LUMENS (Lm)	3600
INPUT VOLTAGE	110/220 VAC	LUMEN EFFICIENCY (Lm/w)	70
FREQUENCY	50/60 Hz	CRI (Ra)	80
LIFE TIME	35,000 Hrs	BEAM ANGLE (°)	120°
WORK TEMPERATURE	-25°C/-45°C	DIMENSION (mm)	Ø 524 x 42
COLOR TEMP (K)	3000-5700 (adjustable)		



Products Distributed by:



INNOVALITE
ELECTRICAL ENTERPRISE

2F Unit F Princeton Square Bldg.,
#35 C. Raymundo Avenue, Rosario, Pasig City, Philippines
Phone Nos.: (02)642-4739 / (02)915-2145; Fax: (02)628-0605 / (02)900-0228
Website: www.innovalitephilippines.com; E-mail: innovalite@yahoo.com